




2024

# AR CONDICIONADO

CATÁLOGO





Life's Good.

# Plasmaster<sup>™</sup>Ionizer<sup>++</sup>

The powerful Plasmaster™ Ionizer++ removes unpleasant odors, along with Escherichia coli and Staphylococcus on surfaces, using over 8 million ions. Experience a safer, cleaner indoor environment.

- \* Specifications may vary for each model.

# **How It Works**

## Reduction and Deodorization (Utilizes Over 8 Million Ions)

Plasmaster Ionizer+ reduces E.coli and Staphylococcus in the surface with over 8 million ions.



## Release of Ions into Air

# Ions are released into the air.

# Surrounding Harmful Substances

H- and O- bond to harmful particles.

## **OH Radical Production**

OH radicals inactivate harmful substances.

#### **Chemical Reaction**

OH radicals bond with H particles.


#### Disinfection

H<sub>2</sub>O molecules are produced.

# Test Result

## **Effective Reduction Performance**

Remove Bacteria E.coli over 99.9% in 20 min




## Test Conditions:

Space: 30m3 Chamber (Measuring with the specimen in the center of test chamber)

Temperature & Humidity: Normal Bacteria: E Coli colon bacillus Verified by Intertek & TUV Rheinland

#### Staphylococcus Sterilization

Remove Staphylococcus aureus over 99.9% in 60 min



## \* Test Conditions :

Space:  $30m^3$  Chamber (Measuring with the specimen in the center of test chamber)

Temperature & Humidity : Normal Bacteria: Staphylococcus Aureus Verified by Intertek & TUV Rheinland

# **Benefit & Verification**

The LGE's ionizer, known as "Plasmaster Ionizer Plus," has demonstrated the capability to remove more than 99.9% of bacteria, including Escherichia coli, Pseudomonas aeruginosa, and Staphylococcus aureus.









# $UV_{nano}^{\mathsf{m}}$


LG DUALCOOL, keeping the fan (inside the unit) 99.99% bacteria-free with ultraviolet light to ensure that the air passing through is clean too.

\*\* UVnano is an integrated marketing name that applies LG Electronics' entire home appliances and it is a compound of the words UV (ultraviolet) and nanometer (unit of length).

# What Is UVnano<sup>TM</sup> and How It Works?

- Emit Ultraviolet rays of UVC wavelength directly damage the DNA of microorganisms (bacteria/mold/viruses) making it impossible for them to multiply.
- High absorption into DNA at 260 to 270 nm wavelengths

# DNA Absorption Efficiency by Wavelength





# **UVC Applied Product**



# **Benefit & Verification**

Keep the fan 99.99% bacteria-clean for a cleaner breeze.



Removes up to **99.99%** of bacteria from the internal fan.



## \* Test Condition

- Test Model : S3NM12JL1GA(SJ), S3NM24K21GA(SK)
- Test Standard : LG test method with referenced to ISO 20743:2007
- Bacteria : Staphylococcus aureus, Staphylococcus epidermidis, Klebsiella pneumoniae


# Allergy Filter

While airflow from an air conditioner may trigger symptoms associated with allergies or asthma, LG units feature an interior filter designed to absorb harmful particles such as dust mites, pollen, fungi, and mold that circulate in the air. This ensures a cleaner and more allergen-free environment.

\* Specifications may vary for each model.

# **How It Works**

Removes allergy-causing substances, such as dust mites that can be found in the air.



# Certification





# Certified by AllergyUK

\* Test Condition Disclaimer

A filter is coated to absorb harmful substances that can cause allergies. The air conditioner strongly absorbs indoor air and removes allergy-causing substances, such as house dust mite, fungi, mold, floating in the air.

Allergy UK (a world-renowned organization) is a British medical charity dedicated to helping adults and children with their allergies. The charity was founded in 1991 as the British Allergy Foundation, and in 2002 the operational name of the charity became Allergy UK. Allergy UK endorses certain products that restrict or remove high levels of allergens and gives them a Seal of Approval.

# **Smart Diagnosis**

Smart Diagnosis allows you to monitor the health of your air conditioner remotely.

- ※ Specifications may vary for each model.
- \* When connected to Multi ODU, Smart Diagnosis function may not be supported.

# What is Smart Diagnosis?

Smart Diagnosis allows users to conveniently check setup, installation, troubleshooting and other information directly from a smartphone.

- $\ensuremath{\mathbb{X}}$  Builds upon widespread smartphone use and offers greater USP diversification
- \* Perfect for consumers who are unable to view information about their air conditioner via a display or remote control.

## **How It Works**

## Embedded Wi-Fi Model

By using "ThinQ" App and clicking "Start Smart Diagnosis", monitor and check diagnosis results conveniently via Wi-Fi.





## Non Embedded Wi-Fi Model





# **Benefit**

Easily understandable error messages simplify the process of identifying solutions and make reaching out to the service center simple and convenient.





## For Consumer



- Easily check the operational status of a product, even without a display or with limited information.
- Save energy by monitoring key operational information and power consumption.
- Utilize the Maintenance Guide to enhance device performance and increase the product's lifespan.

# For Installer and SVC



- Gain a better understanding of the product by easily confirming operational status and information.
- Intuitively diagnose problems by comparing current and past usage data.
- Maintain installation capabilities and reduce errors by quickly confirming device operational status.











LG participates in the ECP programme for EUROVENT AC program.
Check ongoing validity of certification: www.eurovent-certification.com

# **Single Combination**

UNIT				9K	12K	18K	24K
INDOOR				AC09BK NSJ	AC12BK NSJ	AC18BK NSK	AC24BK NSK
	Cooling	Min. / Rated / Max.	kW	0.89 / 2.50 / 3.70	0.89 / 3.50 / 4.04	0.90 / 5.00 / 5.50	0.90 / 6.60 / 7.42
Capacity	Heating	Min. / Rated / Max.	kW	0.89 / 3.30 / 4.10	0.89 / 4.00 / 5.10	0.90 / 5.80 / 6.40	0.90 / 7.50 / 8.64
cupacity	Heating -7°C	Rated	kW	2.60	3.00	4.20	6.00
Power Input	Cooling / Heating	Rated	W	656 / 800	1,080 / 1,050	1,562 /1,611	2,164 / 2,238
EER	cooming / ricating	ridea	W/W	3.81	3.24	3.20	3.05
S.E.E.R.			,	7.00	6.60	7.00	6.90
P design C			kW	2.50	3.50	5.00	6.60
COP			W/W	4.13	3.81	3.60	3.35
S.C.O.P		(Average / Warmer)	**/ **	4.00 / 4.90	4.00 / 4.90	4.30 / 5.30	4.30 / 5.30
P design H (Average	/Marmor)	(Average / Warmer /	kW	2.50 / 1.30	2.50 / 1.30	3.90 / 2.10	5.00 / 2.70
Energy Label	Cooling		KVV	A++	A++	A++	A++
(A+++ to D Scale)	Heating	(Average / Warmer)		A+ / A++	A+ / A++	A+ / A+++	A+ / A+++
	Cooling	(Average / Warmer)	kWh	125	186	250	335
Annual Energy Consumption		(Augrage / Warmer)	kWh	875 / 371	875 / 371	1,270 / 555	
Consumption	Heating	(Average / Warmer)				, .	1,628 / 713
Sound Pressure*	Cooling	S/L/M/H	dB(A)	19 / 27 / 35 / 41	19 / 27 / 35 / 41	31 / 34 / 39 / 44	31 / 34 / 42 / 47
	Heating	L/M/H	dB(A)	27 / 35 / 41	27 / 35 / 41	34 / 39 / 44	34 / 42 / 47
Sound Power	Cooling		dB(A)	59	59	60	65
Air Flow Rate	Cooling	S / L / M / H / Max. (Power)	m³/min	3.0 / 4.2 / 7.5 /	3.0 / 4.2 / 7.5 /	8.0 / 10.5 / 13.0 /	8.0 / 10.5 / 13.1 /
				10.0 / 12.5	10.0 / 12.5	14.5 /15.5	16.1 /18.3
	Heating	L/M/H	m³/min	5.6 / 7.2 / 10.0	5.6 / 7.2 / 10.0	11.0 / 13.5 / 16.0	11.0 / 14.3 / 17.6
Dehumidification Rat		/ /	l/h	1.1	1.3	1.8	2.5
Running Current	Cooling	Min. / Rated / Max.	Α	1.10 / 3.30 / 6.00	1.10 / 4.70 / 6.00	1.20 / 6.90 / 9.00	1.20 / 9.80 / 14.00
	Heating	Min. / Rated / Max.	Α	1.10 / 4.00 / 7.00	1.10 / 4.70 / 7.00	1.20 / 7.10 / 9.50	1.20 / 10.00 / 14.00
Starting Current	Cooling / Heating	Rated	Α	3.30 / 4.00	4.70 / 4.70	6.90 / 7.10	9.80 / 10.00
Power Supply			Ø/V/Hz	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
Circuit Breaker			Α	15	15	20	25
Power Supply Cable			N x mm <sup>2</sup>	3 x 1.0	3 x 1.0	3 x 1.5	3 x 2.5
Power & Transmission Cable			N x mm <sup>2</sup>	4 x 1.0	4 x 1.0	4 x 1.0	4 x 1.0
			IN A IIIIII	(Including Earth)	(Including Earth)	(Including Earth)	(Including Earth)
Dimension			mm	837 x 308 x 192	837 x 308 x 192	998 x 345 x 212	998 x 345 x 212
Net Weight			kg	9.9	9.9	12.8	13.5
Fan Motor Output			W	30	30	30	58
OUTDOOR				AC09BK UA3	AC12BK UA3	AC18BK UL2	AC24BK U24
	Cooling	Min. / Max.	°C DB	-10 / 48	-10 / 48	-15 / 48	-15 / 48
Operation Range	Heating	Min. / Max.	°C DB	-10 / 24	-10 / 24	-10 / 24	-10 / 24
Sound Pressure*	Cooling / Heating	High	dB(A)	48 / 50	48 / 50	53 / 55	54 / 57
Sound Power	Cooling	High	dB(A)	65	65	65	70
Air Flow Rate	,	High	m³/min	27	27	35	49
Piping Piping Connection	Liquid (ODU / IDU)	Min. / Max.	m	3 / 15	3 / 15	3 / 20	3 / 30
	Elevation (ODU / IDU)	Min. / Max.	m	7	7	10	15
	Liquid	OD (Outside)	mm (inch)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)
	Gas	OD (Outside)	mm (inch)	9.52 (3/8)	9.52 (3/8)	12.7 (1/2)	15.88 (5/8)
Drain Hose Size	003	OD (Outside)	mm (inch)	21.5 (27/32)	21.5 (27/32)	21.5 (27/32)	21.5 (27/32)
Diaminose Size	Type	OD (Outside)	min (men)	R32	R32	R32	R32
	туре		lea	0.700	0.700	1.000	1.100
Refrigerant	Charge at 7.5m		kg	0.700	0.700	0.675	0.743
Reirigerant	Additional Chara		t-CO <sub>2</sub> eq				
	Additional Charge GWP		g/m	20	20	20	20
	I-MD		14/	675	675	675	675
For Mater O	GWI		W	43	43	43	85
	GWI			1 T D			
Compressor Type	GWI			Inverter Twin Rotary		Inverter Twin Rotary	
Fan Motor Output Compressor Type Net Weight	GWI		kg	25.1	25.1	34.4	46.0
Compressor Type Net Weight Dimension							
Compressor Type Net Weight			kg	25.1	25.1	34.4	46.0
Compressor Type Net Weight Dimension ACCESSORIES &			kg	25.1	25.1	34.4	46.0
Compressor Type Net Weight Dimension ACCESSORIES & Multi Compatible			kg	25.1	25.1 717 x 495 x 230	34.4	46.0
Compressor Type Net Weight Dimension			kg	25.1	25.1 717 x 495 x 230	34.4	46.0

<sup>\*:</sup> Sound Pressure is not a value declared on Eurovent Program.

<sup>\*</sup> This product contains Fluorinated greenhouse gases (R32).

<sup>%</sup> S : Sleep / L : Low / M : Medium / H : High

 $<sup>\</sup>operatorname{\mathscr{U}}$  GWP : Global warming potential

 <sup>★</sup> t-CO₂eq : F-gas(kg)\*GWP/1000

<sup>\*</sup> For our policy of continuous product improvement, specification, design and feature are subject to change without prior notice.

<sup>\*</sup> Y : Available or Applied / - : Not Available or Not Applied













30 Anos na climatização e tratamento de ar

Delegação de Lisboa Tel: 219 151 792 lisboa@megaclima.pt

Delegação de Queluz Tel: 219 250 028 queluz@megaclima.pt Serviços Centrais

Rua Francisco Ribeirinho, 28

Centro Empresarial Abrunheira – Abrunheira 2710-736 Sintra www.megaclima.pt Escritório 11
Tel: 219 253 300
geral@megaclima.pt